

AMENDMENTS TO THE CLAIMS:

Please amend the claims as follows (this listing of claims will replace all prior versions, and listings, of claims in the application):

1. (Currently amended) Antenna arrangement ~~having the following~~  
~~features comprising:~~
  - at least two antenna element systems ~~(3.1, 3.2)~~ ~~are provided, which each~~  
~~have~~ having at least one antenna element,
  - the at least two antenna element systems ~~(3.1, 3.2)~~ are arranged with an  
offset with respect to one another in the horizontal and/or vertical direction, preferably in  
front of a reflector ~~(2)~~,
  - the at least two antenna element systems ~~(3.1, 3.2)~~ transmitting and receive  
receiving in at least one polarization plane,  
~~characterized by the following further features wherein:~~
    - the at least two antenna element systems ~~(3.1, 3.2)~~ are arranged and/or fed  
such that the main lobe ~~(7.1)~~ of the first antenna element device ~~(3.1)~~ and the main lobe  
~~(7.2)~~ of the second antenna element device ~~(3.2)~~ include an angle ~~( $\theta$ )~~ between one  
another,
    - a network ~~(13)~~ ~~is provided~~ via which the first antenna element system ~~(3.1)~~  
and the second antenna element system ~~(3.2)~~ can be supplied with ~~a signal~~ signals whose  
intensities can be set differently relative to one another, so that it is possible in this way to  
set a different angular transmission direction ~~( $\theta$ )~~ for the antenna arrangement.

2. (Currently amended) Antenna arrangement according to Claim 1, characterized ~~in that~~ wherein the two antenna element systems (3.1, 3.2) are arranged vertically one above the other.

3. (Currently amended) Antenna arrangement according to Claim 1, characterized ~~in that~~ wherein the at least two antenna element systems (3.1, 3.2) are arranged with a horizontal offset with respect to one another.

4. (Currently amended) Antenna arrangement according to ~~one of Claims 1 to 3~~ claim 1, characterized ~~in that~~ wherein at least two columns (23.1, 23.2) are provided, with at least two antenna element devices (3.1, 3.2) being arranged one above the other in each column (23.1, 23.2), by which means the alignment direction of the main lobe, which is produced by superimposition, of the antenna arrangement can be adjusted in the elevation and azimuth directions.

5. (Currently amended) Antenna arrangement according to ~~one of Claims 1 to 4~~ claim 1, characterized ~~in that~~ wherein the network has a hybrid circuit (15, 115a, 115b) and a phase shifter arrangement (17, 117a, 117b), such that the phase shifter arrangement (17, 117a, 117b) allows a signal preferably with the same intensity but at a different phase angle to be supplied to the inputs (15a, 15b) of the hybrid circuit (15, 115a, 115b) such that a signal at the same phase angle but with the different intensity is produced at the output (15'a, 15'b) of each of the hybrid circuits (15, 115a, 115b).

6. (Currently amended) Antenna arrangement according to ~~one of Claims 1 to 5~~claim 1, ~~characterized in that~~wherein the phase shifter arrangement (17, 117a, 117b) is formed from a difference phase shifter.

7. (Currently amended) Antenna arrangement according to ~~one of Claims 1 to 5~~claim 1, ~~characterized in that~~wherein the phase shifter arrangement (17, 117a, 117b) is formed from an arrangement with line paths of different length.

8. (Currently amended) Antenna arrangement according to ~~one of Claims 1 to 7~~claim 1, ~~characterized in that~~wherein the antenna arrangement has at least two antenna element systems, with each antenna element system having at least two antenna elements, with the antenna elements (3.1) in the first antenna element system in each case being arranged offset to one another with respect to the antenna elements (3.2) in the second antenna element system, preferably alternately with respect to one another along a fitting direction.

9. (Currently amended) Antenna arrangement according to ~~one of Claims 1 to 8~~claim 1, ~~characterized in that~~wherein the at least two antenna element systems (3.1, 3.2) each have at least two, and preferably more, antennas or antenna elements (3.1, 3.2) which are arranged interleaved in one another, preferably alternately, in the fitting direction.

10. (Currently amended) Antenna arrangement according to Claim 9, ~~characterized in that~~wherein the distance between the individual antennas or antenna

elements (3.1, 3.2) which are arranged such that they are interleaved is in the region of half the wavelength of the operating frequency.

11. (Currently amended) Antenna arrangement according to ~~one of Claims 1 to 10~~ claim 1, ~~characterized in that~~ wherein the at least two antenna element systems (3.1, 3.2) have two or more antennas and antenna elements (3.1, 3.2) which are arranged interleaved with one another and preferably alternately as antenna elements which are arranged in a plane, in two fitting directions that are at an angle to one another, preferably in two fitting directions that are at right angles to one another, and in that a network (13) is provided, via which the main lobe can be aligned in space by means of a combination of preferably vertical and horizontal control.